

T6 CDD

Recessed Fluorescent Range / Concealed Grid with Diffuser



The flagship range of our recessed luminaire is designed to suit today's growing demands of lighting criteria.

Specification

- Fabricated steel body
- Injection moulded end cap
- Suitable for 15-25mm exposed T grid ceiling
- Suitable for plasterboard ceiling (see optional extra)
- Injection moulded polycarbonate body
- UV stabilised
- Ribbed diffuser

Application

- Reception
- Call Centre
- Circulation Area
- Offices
- Shops
- Conference Room



Product Codes

T6CDD155PZ	1 x 55W PLL
T6CDD255PZ	2 x 55W PLL
T6CDD214FZ	2 x 14W T5
T6CDD314FZ	3 x 14W T5
T6CDD414FZ	4 x 14W T5
T6CDD224FZ	2 x 24W T5
T6CDD324FZ	3 x 24W T5
T6CDD424FZ	4 x 24W T5

Add suffix /EM for 3hr Maintained Emergency

Select End Cap (Set) From Below

End Cap (Set)

OEM-CDX-ECW	White End Cap
OEM-CDX-ECS	Chrome End Cap

Optional Extras

OEM-ATT-01	Plasterboard Recessing Kit
T6CDXSB	Surface Conversion Box

Dimensions

