

Recessed Fluorescent Range / Concealed Grid with Perforated Panel

The flagship range of our recessed luminaire is designed to suit today's growing demands of lighting criteria.

Specification

- · Injection moulded end cap
- · Suitable for 15-25mm exposed T grid ceiling
- · Suitable for plasterboard ceiling (see optional extra)
- · Powder coated perforated steel cover
- · Injection moulded polycarbonate body
- · UV stabilised

Application

- Reception
 Call Centre
 Circulation Area
- · Conference Room

· Offices

·Shops

















Product Codes

T6CDP155PZ 1 x 55W PLL T6CDP255PZ $2 \times 55 W$ PLL T6CDP214FZ $2 \times 14W T5$ T6CDP314FZ 3 x 14W T5 T6CDP414FZ 4 x 14W T5 T6CDP224FZ 2 x 24W T5 T6CDP324FZ 3 x 24W T5 T6CDP424FZ 4 x 24W T5

Add suffix /EM for 3hr Maintained Emergency

Select End Cap (Set) From Below

End Cap (Set)

OEM-CDX-ECW White End Cap
OEM-CDX-ECS Chrome End Cap

Optional Extras

OEM-ATT-01 Plasterboard Recessing Kit
T6CDXSB Surface Conversion Box

Dimensions



