



DENSO PASTE S105

DESCRIPTION Soft brown paste which may be applied underwater by gloved hand, stiff bristle brush or roller. A petrolatum based compound for the preparation of metal surfaces underwater prior to the application of Denso petrolatum tapes. It deposits a layer of protective compound onto the surface such that water is displaced and voids filled when the tape is applied.

COMPOSITION Soft petrolatum containing water displacing, corrosion inhibiting and flow control additives and broad spectrum bactericides. It contains no volatile organic components.

TYPICAL PROPERTIES	DATA
Solids Content	100%
Flash Point	>180°C
Specific Gravity	1.08
Specific Volume	925cc/kg
Coverage	2-5m ² /kg
Temperature Range For Application For Service	5°C to 40°C -25°C to 50°C

SURFACE PREPARATION	Surfaces should be free from mud, loose rust, scale, flaking coatings and marine growth.
----------------------------	--

PACKAGING	2.5kg pails and 25kg drums
------------------	----------------------------

Important

Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request.

Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9002 1994 (Certificate No. FM01548).

Winn & Coales (Denso) Ltd, Denso House, Chapel Road, London SE27 0TR, United Kingdom
Tel: +44 (0) 20 8670 7511 Fax: +44 (0)20 8761 2456 Email: mail@denso.net Website: www.denso.net