



PPLASTIPACK LIMITED

Manufacturers of Energy and Resource Saving Products

540 Grade

TECHNICAL SPECIFICATION DATA



ENGLISH	
Polyethylene Film	Dual-Extruded
U.V. Protection	HALS
Colouring	Light Grey / Black
Thermal Properties	Vicat Softening Point (1kg) 93°C
Cold Crack Temperature	-25°C
540 microns thickness	Bubble Film = 300µm +/- 10% Back Film = 240µm +/- 10%
Weight per m ²	520gms +/- 10%
Overall Bubbles Width	2500mm +/- 1%
Welding Edges	50mm +/- 10%
Overall Width	2600mm +/- 10%
Roll Diameter	0.80 metres +/- 1%
Roll Length	90 metres +/- 2%
Estimated Quantity for 120m ³ truck	2.5m = 14,535 m ² = 57 rolls
Estimated Quantity for Containers (2000mm)	20ft = 4050 m ² = 18 rolls 40ft = 10125 m ² = 45 rolls
Packaging	Packaged in Polyethylene bags
Core Diameters	Internal 76mm/External 80mm
Identification	Batch Identification by Q.A slip and label showing Length/Grade
GEOBUBBLE™ TECHNOLOGY	
Bubble Width x Length	15 x 30 mm
Bubble Height	5.5mm
No. of bubble per m ²	1029

FRANCAISE	
Film Polyéthylène	Dual-Extrudé
Anti-U.V.	HALS
Quantité de Coloration	Clair Gris / Noir
Les Propriétés thermiques	Vicat Amollissant le Point (1kg) 93°C
Température fissuration à froid	-25°C
Epaisseur de la 500 micron	Pellicule supérieure = 300µm +/- 10% Pellicule inférieure = 240µm +/- 10%
Poids par m ²	520gms +/- 10%
Largeur totale des bulles	2500mm +/- 1%
Largeur d'une bordure	50mm +/- 10%
Largeur totale avec bordures	2600mm +/- 10%
Diametre du Rouleau	0.80 mètres +/- 1%
Longueur du rouleau	09 mètres +/- 2%
Quantité moyenne par camion de 120m ³	2.5m = 14535 m ² = 57 Rouleaux
Quantité moyenne par conteneur (2000mm)	20ft = 4050 m ² = 18 Rouleaux 40ft = 10125 m ² = 45 Rouleaux
Conditionnement	Sac en Polyéthylène
Diamètre	Interne 76mm/Externe 80mm
Identification	Identification du lot par fiche Qualité et étiquette indiquant longueur et
TECHNOLOGIE GEOBUBBLE™	
Largeur x longueur de la bulle	15 x 30 mm
Hauteur de la bulle	5.5mm
Nombre de bulles par m ²	1029



With GeoBubble™ Technology

Plastipack Limited, Wainwright House, 4 Wainwright Close, Churchfields Industrial Estate, St Leonards-on-sea TN38 9PP, UK

Tel: +44 (0) 1424 851 659 Fax: +44 (0) 1424 853 909

CoolGuard™, EnergyGuard™, Sol+Guard™, GeoBubble™ and VapourGuard™ are trademarks of Plastipack Limited.

Patent applied for CoolGuard™ No. 0820437.2, EnergyGuard™ No. 0820440.6, Sol+Guard™ No. 820435.6 and GeoBubble™ No.

PCT/2010/001851

www.Plastipack.co.uk | www.GeoBubble.co.uk | www.VapourGuard.com

