



LEGEND:

- EXISTING STRUCTURE TO BE RETAINED
- NEW REINFORCED CONCRETE STRUCTURE
- NEW BRICKWORK
- NEW LOADBEARING BLOCKWORK
- B1 - NEW STEEL BEAM AND REFERENCE. REFER TO SCHEDULE FOR TYPE AND SIZE
- P1 - NEW PADSTONE AND REFERENCE. REFER TO SCHEDULE FOR TYPE AND SIZE
- C1 - COLUMN REFERENCE
- COLUMN BELOW SYMBOL
- TWO-WAY SPAN OF RC SLAB. REFER TO LAYOUT FOR DEPTH.
- ONE-WAY SPAN OF RC SLAB. REFER TO LAYOUT FOR DEPTH.
- PRECAST CONCRETE PLANKS
- SPAN OF 50x175mm DEEP GRADE C24 TAMBER JOISTS AT 400mm c/c WITH 1% LAYER OF 18mm F.V. SHEATHING TOP
- STEP IN LEVEL SYMBOL
- L1 - CAST IN CHANNEL FOR MASONRY SUPPORT ANGLE BY HALFEN OR SIMILAR. LENGTH TO SUIT CLEAR WINDOW OPENING.

ABBREVIATIONS:

- FL - FORMATION LEVEL
- SSL - STRUCTURAL SLAB LEVEL
- FEL - FINISHED FLOOR LEVEL
- TOF - TOP OF FLOOR
- TOB - TOP OF BEAM
- TOPC - TOP OF PILECAP
- TOS - TOP OF STEEL
- TOW - TOP OF WALL
- L1 - LOW LEVEL
- H1 - HIGH LEVEL
- CR - STEEL BEAM CRANK LINE

REF.	SIZE	COMMENTS
C2	300mm DIA. RC COLUMN	
C4	250mm DIA. RC COLUMN	
C5	200x510mm RC COLUMN	
C6	200x450mm RC COLUMN	
C7	300x620mm RC COLUMN	

DRAINAGE POSITIONS SHOWN INDICATIVELY REFER TO ARCHITECT FOR SETTING OUT