

WORKING with FILON GRP Guide to Handling and COSHH Regulations

Industrial Health and Safety Information

Guide to Handling

Identification

Product

FILON glass reinforced polyester (GRP) sheeting.

Constituents

Glass fibres, polyester resins, inert fillers, UV stabilisers, promoters and flame retardants.

Identification

Continuous nylon threads at 12mm centres and labels identify profile and grade.

Material Use

Mainly utilised for rooflights and internal linings in buildings. When required for alternative applications consult Filon Products Limited before use.

Protection

Personnel: Siteworks

Do **NOT** walk on sheets, ALWAYS use crawling boards. Although sheets will be designed to be 'NON-FRAGILE' for the specific application, to prevent any deflections caused by point loading from damaging the sheets or sealants, crawling boards **MUST** always be used when fixing and carrying out maintenance work.

Attention is drawn to the Health and Safety Executive Guidance Note HS(G)33 "Safety in Roof Work", published by HMSO. Also, to ACR[CP]001:2003 "Recommended Practice for Work on Profiled Sheeted Roofs", a best practice guide by the Advisory Committee for Roofwork.

To avoid injury appropriate P.P.E **must** be worn at all times when handling GRP products.

Personnel : Public

FILON GRP sheets have been tested under the conditions laid down in **BS476 "Fire Tests"**. Facsimiles of test results are available on request.

The following regulations which control the use of FILON sheets on buildings within the UK must be complied with :

- **The Building Regulations (England and Wales).**
- **The Building Standards (Scotland) Regulations.**
- **The Building Regulations (Northern Ireland).**

COSHH Regulations

Protection

Personnel : Re-working and Machining

When cutting or machining with power tools, a non toxic biological inert dust is produced. These dust levels should be kept as low as reasonably practical, and must not exceed the **Occupational Exposure Limit of 10mg/m³ total inhalable dust and 4mg/m³ respirable dust - 8 hour TWA value.**

When working *out of doors*, it is most unlikely that these levels could be reached. When working *indoors* or in a confined spaces, adequate ventilation should be provided, and when extensive operations are necessary, suitable dust extraction should be provided.

Operators should wear suitable dust masks and goggles.

In isolated cases, GRP dust may cause a slight transient irritation. Should these effects be prolonged or any signs of a rash occur, medical advice must be obtained.

All exposed skin must be thoroughly and frequently washed with soap and water. Any eye contamination must be washed with copious amounts of sterile or clean water.

Do not smoke in or near stores or working areas.

Storage

All FILON sheets will burn giving off black toxic smoke which can include hydrogen chloride and hydrogen bromide fumes. Suitable extinguishers include dry powder, carbon dioxide, foam and water spray. Wear self-contained breathing apparatus.

Disposal

FILON GRP is an inert product. Scrap and waste sheets should only be disposed of at approved land fill sites.

Technical Services

Technical and advisory services are available from Area Sales Managers or Filon Technical Services Department.

For further information about the Company, its Products and Services please visit our web site www.filon.co.uk.

In addition, there is a general product datasheet entitled “**FILON PRODUCTS - More than just glassfibre sheet for roofing and cladding**” outlining the range of products manufactured by the Company and their applications.

FILON is a trademark of Filon Products Ltd.

Information and recommendations contained in this publication are given in good faith without warranty or guarantee. Because we are constantly seeking to improve our products, we reserve the right to change specifications at any time. No liability can be accepted for any claims, losses or demands arising out of the contents of this publication. This statement does not affect any statutory rights which cannot be excluded by agreement.



FILON®

Filon Products Limited

Unit 3 Ring Road Zone 2 Burntwood Business Park
Burntwood Staffordshire England WS7 3JQ

Tel 01543-687-300 Fax 01543-687-303

e-mail : sales@filon.co.uk website : www.filon.co.uk